




## **SOLICOR Compact: 560, 596, 597, 598, 599 (Excludes finishes 31, 95, 96)** **Wilsonart**

**Final Assembly:** Fletcher, North Carolina, USA

**Life Expectancy:** 20-50 Year(s)

**Embodied Carbon:** 2.91E+01 KG CO2 EQ. 

**Declared Unit:** ONE SQUARE METER OF PRODUCT

**End of Life Options:** Landfill (100%)

**EU CoC Screened:** Does Not Contain

### **Ingredients:**

**SOLICOR Compact:** Wood / Cellulose Fiber (Kraft / Decorative / Overlay); **Melamine Resin<sup>1</sup>**; Titanium dioxide; Black Pigment; Grit; Release

<sup>1</sup>LBC Temp Exception RL-009 - Formaldehyde

### **Living Building Challenge Criteria:** Compliant

#### **I-13 Red List:**

- |   |                             |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free                | % Disclosed: 100% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared                         |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Product Available with FSC Chain of Custody

WIL-0004

EXP. 01 MAR 2025

SCREENED: 26 FEB 2024

Original Issue Date: 2023