

# Declare.

## SOLICOR Laminate: 160, 161 Wilsonart

**Final Assembly:** Temple, Texas, USA

**Life Expectancy:** 20-50 Year(s)

**Embodied Carbon:** 1.99E+00 KG CO2 EQ

**Declared Unit:** 1 SQUARE METER OF PRODUCT

**End of Life Options:** Landfill (100%)

**EU CoC Screened:** Does Not Contain

### Ingredients:

**SOLICOR Laminate:** Wood / Cellulose Fiber (Kraft / Decorative / Overlay); **Melamine Resin<sup>1</sup>**; **Phenolic Resin<sup>1</sup>**; Titanium dioxide; Black Pigment; Colorant; Grit; Release

<sup>1</sup>LBC Temp Exception RL-009 - Formaldehyde

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- LBC Red List Free                      % Disclosed: 100% at 100ppm
- LBC Red List Approved                VOC Content: Not Applicable
- Declared

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Product Available with FSC Chain of Custody

WIL-0006

EXP. 01 MAR 2024

SCREENED: 07 FEB 2023

Original Issue Date: 2023