

Declare.

High Pressure Laminate (HPL) - Types: 107, 174, 335, 350, 362, 364, 366, 367, 372, 374, 376, 377 Wilsonart

Final Assembly: Temple, Texas, USA; Fletcher, North Carolina, USA

Life Expectancy: 20 - 50 Year(s)

Embodied Carbon: 1.99E+00 kg CO2 eq

Declared Unit: 1 square meter of product

End of Life Options: Landfill (100%)

EU CoC Screened: Does Not Contain

Ingredients:

High Pressure Laminate: Wood / Cellulose Fiber (Kraft / Decorative / Overlay); **Melamine Resin¹**; **Phenolic Resin¹**; Black Pigment; Grit; Yellow Pigment; Colorant; Catalyst; Release; Release

¹LBC Temp Exception RL-009 - Formaldehyde

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Product Available with FSC Chain of Custody

WIL-0001

EXP. 01 MAY 2023

SCREENED: 01 FEB 2023

Original Issue Date: 2022

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare