

# Declare.

## High Pressure Laminate (HPL) - Types: 107, 174, 335, 350, 362, 364, 366, 367, 372, 374, 376, 377 Wilsonart

**Final Assembly:** Temple, Texas, USA; Fletcher, North Carolina, USA

**Life Expectancy:** 20 - 50 Year(s)

**Embodied Carbon:** 1.99E+00 kg CO2 eq 

**Declared Unit:** 1 square meter of product

**End of Life Options:** Landfill (100%)

**EU CoC Screened:** Does Not Contain

### Ingredients:

**High Pressure Laminate:** Wood / Cellulose Fiber (Kraft / Decorative / Overlay); **Melamine Resin<sup>1</sup>**; **Phenolic Resin<sup>1</sup>**; Black Pigment; Grit; Yellow Pigment; Colorant; Catalyst; Release; Release

<sup>1</sup>LBC Temp Exception RL-009 - Formaldehyde

### Living Building Challenge Criteria: Compliant

#### I-13 Red List:

- LBC Red List Free      % Disclosed: 100% at 100ppm
- LBC Red List Approved      VOC Content: Not Applicable
- Declared

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Product Available with FSC Chain of Custody

WIL-0001

EXP. 01 MAY 2024

SCREENED: 03 MAR 2023

Original Issue Date: 2022